



# PANpilot : « pilots everything for your water »

**Use :** Regulate the pH and the chlorine by Redox \*, for pools up to 300 m<sup>3</sup>

**Chlore :**  
Pump dosing 8 l/h.

**pH\*\* :**  
Pump dosing 3l/h\*

Practice: the light into the panel to hide the sons behind.

Room of analysis with gate of taking of sample and flux detection

Panel dimensions  
58 x 38 x 20 cm



**Optional kit in demand**  
Connect the PANpilot to the web.

**Free web access**  
No setting needed. AvadyConnect is linked to internet by a cable. PROpilot communicates by radio with the AvadyConnect (50 m maxi). Only one table to manage all your pools. Change from distance PROpilot's parameters, and receive lack chemical alerts, data history and graphs. Visit [www.avadyconnect.com](http://www.avadyconnect.com) -ID demo - password: demo

## Supplied kit of installation



### INNOVATIVE

- PROpilot regulates simultaneously the pH and the chlorine levels\*
- It displays simultaneously the pH and the redox (chlorine level) values

\* For a correct redox measure, ensure that the pool stabilizer level is under 15ppm (15mg/l)  
\*\* incompatible with hydrochloric acid

### MULTIPURPOSE

- Designed for private (30 to 300m<sup>3</sup>) and public pools (30 to 220m<sup>3</sup>).

### SECURE

- Volumetric alarm avoiding emptying of the chemical tank
- Adjusts the dosing depending on the pH and chlorine chemical needs
- Flux detection in the chamber



**AVADY POOL** - 9, Chaussée Jules César, Bâtiment 4 Hall 406 - 95520 OSNY - France  
Tel : +33 (0)1 34 48 16 03 - Fax : +33 (0)1 78 76 73 95  
Email : [contact@avadypool.com](mailto:contact@avadypool.com) - Web : [www.avadypool.com](http://www.avadypool.com)

It is the responsibility of the user to ensure that these products are in line with their needs.