

PANpilot® S20



Simultaneously regulates pH and chlorine levels (mV)

Suitable for campsites, hotels, residential complexes and balneotherapy facilities requiring little stabiliser

Private
pools

Public
pools

Hot
tubs

- pH**:
3 l/h metering pump



- Panel dimensions:
58 x 38 x 20 cm



- Chlorine:
8 l/h metering pump



- Professional analysis chamber:
 - Redox sensor
 - pH sensor
 - Flow detection
 - Sampling valve



EFFICIENT

- PANpilot® simultaneously regulates pH and chlorine* levels.
- It simultaneously displays the redox and pH values.
- The electromagnetic pump is ideal for dispensing chlorine.
- Combined technologies (peristaltic pump for pH / electromagnetic membrane for chlorine) for versatility and resistance
- The sensors are protected against induced electric currents in the water.

SAFE

- Volumetric alarm preventing the chemical container running dry
- Dosage proportional to pH and chlorine requirements

VERSATILE

- Intended for private pools from 30 to 300 m³ and public pools from 30 to 220 m³.

WARRANTY

- Device: two years | Sensors: one year

- Supplied with a **complete kit** for quick and easy installation:



* To ensure correct redox measurement, make sure that the stabiliser content in the pool does not exceed 15 ppm (15 mg/l).

** Incompatible with hydrochloric acid