

MAGNET S10

Easy-to-use electromagnetic metering pump for the dosage of chlorine dosage and pH products

- Combined with a pH or chlorine regulator, it serves to **automatically** dose the products used to treat the water in swimming pools.
- Used alone, it provides a constant dose of the product.
- The product delivery rate is adjusted by means of a selector switch on the front panel, which can be adjusted from 20% to 100% of the pump's maximum output.
- Quiet pump equipped with a sound attenuator.
- Wall-mounted dimensions: 159 x 106 x 143 mm
Dimensions on stand: 188 x 106 x 143 mm



TECHNICAL SPECIFICATIONS

Type	Max. output	Max. pressure	Min./max. pulses	Dose per pulse	Suction height	Standard elec. supply	Cons.	Net weight
	l/h	bar		ml	m	Volts - Hz	Watts	Kg
2-3	2	3	120	0.27	1.5	220/240 V 50-60 Hz	32	1.9
6-3	6	3	120	0.83	1.5	220/240 V 50-60 Hz	32	1.9

- The mounting bracket can be fastened to a wall or to a dispensing container.



- Supplied with a **complete kit** for quick and easy installation:



• Standard equipment:

- Pump head: PP (option: PVDF, PVC)
- Membrane: Teflon
- Trims: FPM (Viton[®]) (option: EPDM (Dutral[®]))
- Check valves: lip valve (option: glass or ceramic beads)