

# MAGNET S10

Easy-to-use electromagnetic metering pump for the dosage of chlorine dosage and pH products

- Combined with a pH or chlorine regulator, it serves to **automatically** dose the products used to treat the water in swimming pools.
- Used alone, it provides a constant dose of the product.
- The product delivery rate is adjusted by means of a selector switch on the front panel, which can be adjusted from 20% to 100% of the pump's maximum output.
- Quiet pump equipped with a sound attenuator.
- Wall-mounted dimensions: 159 x 106 x 143 mm  
Dimensions on stand: 188 x 106 x 143 mm



## TECHNICAL SPECIFICATIONS

| Type | Max. output<br>l/h | Max. pressure<br>bar | Min./max. pulses | Dose per pulse<br>ml | Suction height<br>m | Standard elec. supply<br>Volts - Hz | Cons.<br>Watts | Net weight<br>Kg |
|------|--------------------|----------------------|------------------|----------------------|---------------------|-------------------------------------|----------------|------------------|
| 2-3  | 2                  | 3                    | 120              | 0.27                 | 1.5                 | 220/240 V 50-60 Hz                  | 32             | 1.9              |
| 6-3  | 6                  | 3                    | 120              | 0.83                 | 1.5                 | 220/240 V 50-60 Hz                  | 32             | 1.9              |

- The mounting bracket can be fastened to a wall or to a dispensing container.



- Supplied with a **complete kit** for quick and easy installation:



- **Standard equipment:**
  - Pump head: PP (option: PVDF)
  - Membrane: Teflon
  - Trims: FPM (Viton<sup>®</sup>) (option: EPDM (Dutral<sup>®</sup>))
  - Check valves: lip valve (option: glass or ceramic beads)

2L/h = AYPO241002039A020  
6L/h = AYPO241006039A020

AVADY POOL | 9 Chaussée Jules César · Bât 4 Hall 406 · 95520 OSNY · France

Tel.: +33 1 34 48 16 03 | contact@avadypool.com | www.avadypool.com

Users are responsible for ensuring that these products meet their needs.

