PANpilot pH Rx

Simultaneously regulates pH and chlorine or bromine levels (mV)

Suitable for controlling an electrolytic cell or the dissolution of chlorine or bromine tablets.





• pH**: 3L/h metering pump



• Chlorine or bromine output: 230 VAC outlet with pre-wired power connections

> • Panel dimensions: 58 x 38 x 15 cm



- Professional analysis chamber:
 - Redox sensor
 - pH sensor
 - Flow detection - Sampling valve





INNOVATIVE

- PANpilot® simultaneously regulates pH and chlorine* or bromine
- It simultaneously displays the redox value (chlorine content (mV)) and the pH value.
- The sensors are protected against induced electric currents in the water.

SAFE

- Volumetric alarm preventing the chemical container running dry
- Dosage proportional to pH and chlorine requirements
- Jack input connectors for detection of empty pH and chlorine containers

VERSATILE

- Intended for public pools (up to 200m³) and private pools (up to 300m³)
- Chlorination: select the appropriate chlorination method (electrolytic cell, dosing pump, solenoid valve).
- Suitable for an attendance of 1person/2m³/day.

WARRANTY

Device: two years | Sensors: one year



AvadyConnect® Web Interface



Device predisposed to receive the AVADYCONNECT® option to remotely consult and control pool related data.



ADVANTAGE A single dashboard to remotely manage the maintenance of all your pools. You can now remotely change device settings, receive low level of product alerts, check data history and graphs etc.

AYAC100383



^{*} To ensure correct redox measurement, make sure that the stabiliser content in the pool does not exceed 15 ppm (15 mg/l).

^{**}Incompatible with hydrochloric acid