

MAGNET S10

Easy-to-use electromagnetic metering pump for the dosage of chlorine dosage and pH products.



- Combined with a pH or chlorine regulator, it serves to **automatically** dose the products used to treat the water in swimming pools.
- Used alone, it provides a constant dose of the product.
- The product delivery rate is adjusted by means of a selector switch on the front panel, which can be adjusted from 20% to 100% of the pump's maximum output.



2L/h = AYP0241002039A020
6L/h = AYP0241006039A020



Scan to discover !

- Quiet pump equipped with a sound attenuator.
- Wall-mounted dimensions: 159 x 106 x 143 mm
Dimensions on stand: 188 x 106 x 143 mm
- Device guaranteed for two years.

TECHNICAL SPECIFICATIONS

Type	Max. output l/h	Max. pressure Bar	Min./max pulses	Dose per pulse ml	Suction height m	Standard elec. supply Volts - Hz	Cons. Watts	Net weight Kg
2-3	2	3	120	0,27	1,5	220/240 V 50-60 Hz	32	1,9
6-3	6	3	120	0,83	1,5	220/240 V 50-60 Hz	32	1,9

- The mounting bracket can be fastened to a wall or to a dispensing container.



- Delivered with a **complete kit** for quick and easy installation :



- **Standard equipment:**

- Pump head: PP (option: PVDF)
- Membrane: Teflon
- Trims: FPM (Viton[®]) (option: EPDM (Dutral[®]))
- Ceramic ball valve