

PANduo pH CLM (1,5-1,5L/h)



Simultaneously regulates pH and chlorine levels (ppm)
Suitable for public spas, paddling pools, balneotherapy facilities and aqua-bike cabins



- Live display of the **pH value** and of the **chlorine content (in ppm)**



- Supplied with two 1,5L/h peristaltic pumps for pH and chlorine dosage



HIGH PERFORMANCE

- Quick response from the chlorine sensor, enabling regulation in small volumes of water (hot tubs, balneotherapy, pools).
- Measures pH and the concentration of free chlorine
- Measurement scales: pH from 0 to 14 and chlorine from 0 to 5 ppm.
- Closed amperometric sensor (not sensitive to pH) compatible with stabiliser (up to 80 ppm)

SIMPLE

- Pre-assembled panel that is easy to wall-mount using the installation accessories provided

SAFE

- Jack input connectors for detection of empty pH and chlorine containers
- Option: Jack input connectors for temperature detectors (AYAC100605)

VERSATILE

- Intended for public pools from 1 to 30 m³ and private pools from 1 to 60 m³
- Compatible with:
 - Organic and inorganic chlorine
 - Stabiliser up to 80 ppm

WARRANTY

- Device: two years



AvadyConnect® Web Interface

Device predisposed to receive the **AVADYCONNECT®** option to remotely consult and control pool related data.



ADVANTAGE A single dashboard to remotely manage the maintenance of all your pools. You can now remotely change device settings, receive low level of product alerts, check data history and graphs etc.

Discover our web interface at www.avadyconnect.com; username and pw: demo

AYAC100383