

DUO pH[®] Turboxy



Simultaneously regulates pH and chlorine levels (ppm)
Suitable for hotels and residential complexes

Private
pools

Public
pools
ars



- Integrated dosage of pH and chlorine
 - Quiet peristaltic pumps



INNOVATIVE

- DUO pH Turboxy simultaneously regulates pH* and chlorine levels.
- It simultaneously displays the Cl value (chlorine content in mg/L), the pH value, and the temperature.
- The sensors are protected against induced electric currents in the water.

SAFE

- Volumetric alarm preventing the chemical container running dry
- Dosage proportional to pH and chlorine requirements
- Jack input connectors for detection of empty pH and chlorine containers
- Flow switch incorporated in the Turboxy sensor

VERSATILE

- Compatible with the presence of stabiliser in the water (from 0 to 50 ppm)
- Integrated pumps: pH 1.5L/h and chlorine 3L/h
- Compatible with organic and inorganic chlorine
- Intended for private pools up to 150 m³ and public pools up to 90 m³

WARRANTY

- Device: two years | pH sensor: one year


INSTALLATION RECOMMENDATIONS

- Assembly on horizontal DN 50 pipe
- Filtration pump flow rate between 5 m³/h and 12 m³/h for installation on a pipe:
 - If flow rate < 8 m³/h: installation of the TBX remote kit (10000020).
 - If flow rate < 12 m³/h: install in bypass configuration.
- At over 30°C, use a B10 impeller (10000019).
- Compatible with water containing stabiliser up to 40 ppm.



Two-in-one sensor holder

- A single location for measurement and injection
- Sensor fully protected by the sensor holder tube
- Compatible with DN50 and DN63 pipes
- A winterisation plug is provided to replace the sensor in the sensor holder.
- Horizontal or vertical assembly



AvadyConnect[®] Web Interface



Device predisposed to receive the **AVADYCONNECT[®] option** to remotely consult and control pool related data.



ADVANTAGE A single dashboard to remotely manage the maintenance of all your pools. You can now remotely change device settings, receive low level of product alerts, check data history and graphs etc.

Discover our web interface at www.avadyconnect.com; username and pw: demo

AYAC100383

* Incompatible with hydrochloric acid

AYPO16025

AVADY POOL | 9 Chaussée Jules César · Bât 2 Porte 221 B · 95520 OSNY · France

Tel.: +33 1 34 48 16 03 | contact@avadypool.com | www.avadypool.com

Users are responsible for ensuring that these products meet their needs.

