

POOLeasY® Salt



Saltwater chlorination treatment

Suitable for pools from 45 to 175m³ depending on the model

Private Pools



Scan to find out!

- Low Salt/Normal Salt compatible
 - Permanent display of chlorine production
- Led matrix display with 2-button interface
- Indicator light alarms



INNOVATIVE

- Power Control technology for stable chlorine production in all circumstances (worn cell, low salt, etc.)
- Production mode adjustable at installation for operation from **1.5 g/L in Low Salt (LS)** or **2.5 g/L in Normal-Salt (NS)** with no upper limit

SIMPLE

- Chlorine production adjustable from 0 to 10
- Automatic self-cleaning of the cell by polarity inversion adjustable according to water hardness
- Safety devices: low water, low salt, cell fault.

COMPLETE

- Supplied with a high-quality transparent cell to accommodate a flow sensor (optional) and pH injection.

VERSATILE

- Cover mode to modulate chlorine production according to the position of the cover
- Boost mode for superchlorination for 24 hours
- 4 versions available: suitable for pools from 45 to 175m³

WARRANTY

- Device : 2 years | Cell : 3 years

Designation	Reference	Prod° NS		Prod° LS	
		g/h	m ³	g/h	m ³
POOLeasY SALT 9-7	ELLY23AYSB-G0HX09	9	45	7	35
POOLeasY SALT 16-12	ELLY23AYSB-G0HX16	16	80	12	60
POOLeasY SALT 26-18	ELLY23AYSB-G0HX26	26	130	18	90
POOLeasY SALT 35-29	ELLY23AYSB-G0HX35	35	175	29	145