

# PANpilot pH® Turboxy S20



Simultaneously regulates pH and chlorine levels (ppm)  
*Suitable for campsites, hotels and residential complexes.*



- Live display of the **chlorine content in ppm**, of the **pH value** and of the temperature



- Peristaltic pump for pH (3L/h)



- Panel dimensions: 58 x 38 x 20 cm



- Magnetic pump for chlorine (8L/h)



- Professional analysis chamber:
  - Turboxy® chlorine sensor
  - pH sensor
  - Flow switch **Flw**
  - Sampling valve

Private Pools

Public Pools



AYPA1217



Scan to discover !

## INNOVATIVE

- PANpilot pH® Turboxy S20 simultaneously regulates pH and chlorine levels.
- Thanks to patented Turboxy® technology, the analysis chamber is compact, making maintenance easier.
- The sensor is protected against induced electric currents in the water.

## SAFE

- Volumetric alarm preventing the chemical container running dry.
- Dosage proportional to pH and chlorine requirements.
- The Turboxy® sensor has an integrated flow switch and temperature sensor.
- Jack input connectors for detection of empty pH and chlorine containers.

## COMPLETE

- Delivered with a **complete kit** installation for quick and easy :



## VERSATILE

- Intended for public pools (from 5 to 220 m<sup>3</sup>) and private pools (from 5 to 300 m<sup>3</sup>).
- Compatible with:
  - Organic and inorganic chlorine
  - Stabiliser up to 50 mg/l

## WARRANTY

- Device: two years | pH sensor: one year

## AvadyConnect® Web Interface



By installing the **optional AVADYCONNECT® COMMUNICATION KIT**, this device will allow the user to remotely consult and control pool related data.



**ADVANTAGE** A single dashboard to remotely manage the maintenance of all your pools. You can now remotely change device settings, receive low level of product alerts, check data history and graphs etc.

Discover our web interface at [www.avadyconnect.com](http://www.avadyconnect.com); username and pw: demo

AYAC100524