# PANduo pH® Turboxy




# Simultaneously regulates pH and chlorine levels (ppm)

Suitable for campsites, hotels, residential complexes.





AYPA1216 = Without Avady Connect



 Peristaltic pump for chlorine (3L/h)





- Professional analysis chamber:
  - Turboxy® chlorine sensor
  - pH sensor
  - Flow switch
  - Sampling valve



### **INNOVATIVE**

- PANduo pH Turboxy simultaneously regulates pH and chlorine
- Thanks to patented Turboxy® technology, the analysis chamber is compact, making maintenance easier.

• Live display of the **chlorine content** 

in ppm, of the pH value and of the temperature

> Peristaltic pump for pH (1.5L/h)

 Panel dimensions: 58 x 38 x 17 cm

- Features an abrasive impeller for stable chlorine measurement.
- The sensor is protected against induced electric currents in the water.

#### **SAFE**

- Volumetric alarm preventing the chemical container running dry.
- Dosage proportional to pH and chlorine requirements.
- Jack input connectors for detection of empty pH and chlorine containers.
- The Turboxy® sensor has an integrated flow switch and temperature sensor.

#### **COMPLETE**

• Delivered with a **complete kit** for guick and easy installation :



#### **VERSATILE**

- Intended for public pools (up to 90 m³) and private pools (up to 150 m<sup>3</sup>).
- Compatible with:
  - Organic and inorganic chlorine
  - Stabiliser up to 50 mg/l

#### WARRANTY

• Device: two years | pH sensor: one year

#### INSTALLATION RECOMMENDATIONS

• At over 30°C, use a B10 impeller (10000019).

## Web AvadyConnect® Interface



By installing the optional AVADYCONNECT® COMMUNICATION KIT, this device will allow the user to remotely consult and control pool related data.



ADVANTAGE A single dashboard to remotely manage the maintenance of all your pools. You can now remotely change device settings, receive low level of product alerts, check data history and graphs etc.

Discover our web interface at www.avadyconnect.com; username and pw: demo

AYAC100524

