Photos not contractually binding



MAGNET S20 pH or Rx

Easy-to-use electromagnetic metering pump for the dosage of chlorine dosage and pH products.

AYPO232008039A010 (pH) AYPO233008039A010 (Rx)



Scan to discover!

- Pump equipped with a regulator to measure pH or the redox
- **Proportional** dosage, based on requirements, of water treatment products for swimming pools.
- Measurement scale:
 - pH from 0 to 14
 - Redox from 0 to 1000 mV
- Equipped with a four-pole input to connect a suction nozzle (optional) and manual drain
- The product delivery rate can be adjusted by means of a selector switch with two scales:
 - 20% to 100% of maximum output
 - 4% to 20% of maximum output
- Quiet pump equipped with a sound attenuator (up to 8 l/h)*
- Dimensions: 120 × 210 × 149 mm
- 4-pole connector for empty container detectors



TECHNICAL SPECIFICATIONS								
Type	Max. output	Max. pressure	Min./max pulses	Dose per pulse	Suction height	Standard elec. Supply	Cons.	Net weight
	l/h	bar		ml	m	Volts – Hz	Watts	Kg
8 - 3*	8	3	120	1,67	1,5	230 V 50-60 Hz	58	2,9
12 - 3	12	3	120	2,22	1,5	230 V 50-60 Hz	58	2,9

• Delivered with a **complete kit** for quick and easy installation :



Standard equipment: Pump head: PVDF Membrane: Teflon

- Trims: FPM (Viton ®) (option: EPDM (Dutral ®))

- Max. frequency: 120 strokes/minute

